



PK132 (v4.0) December 23,
2011

100% Material Declaration Data Sheet VOG48

Pure Tin Leads*

*Xilinx Platform Flash PROM VOG48 with datecode prior to 1030 will have Matte Tin (Sn) Lead-frame plating finish

Average Weight: 0.520 g

Component	Substance Description	CAS# or Description	% of Component	Use in Product	Component Weight/ Substance Weight (in grams)	Component % of Total
Silicon die					0.003864	0.743%
	Silicon	7440-21-3	99.70		0.003850	
	Aluminium (Al)	7429-90-5	0.20		0.000010	
	Copper (Cu)	7440-50-8	0.05		0.000002	
	Titanium	7440-32-6	0.05		0.000002	
Lead-frame alloy					0.109060	20.973%
	Copper (Cu)	7440-50-8	97.25		0.106060	
	Iron (Fe)	7439-89-6	2.35		0.002560	
	Zinc (Zn)	7440-66-6	0.12		0.000130	
	Iron Phosphide (FeP)	26508-33-8	0.08		0.000090	
	Silver (Ag)	7440-22-4	0.20		0.000220	
Lead-frame plating					0.003140	0.604%
	Tin (Sn)	7440-31-5	100.00		0.003140	
Die Attach Material					0.000760	0.146%
	Silver	7440-22-4	79.00		0.000600	
	Bismaleimide and acrylate polymer	Trade Secret	14.00		0.000110	
	Acrylate monomer	Trade Secret	7.00		0.000050	
Gold Wire					0.000670	0.129%
	Gold	7440-57-5	100.00		0.000670	
Mold Compound Encapsulation					0.402500	77.404%
	Epoxy Resin	Trade Secret	8.00		0.032200	
	Phenol Resin	Trade Secret	8.00		0.032000	
	Silicon Dioxide	60676-86-0	83.50		0.336090	
	Carbon Black	1333-86-4	0.50		0.002010	

** Xilinx Platform Flash PROM VOG48 with datecode 1030 or after will have NiPdAu Lead-frame plating finish

Average Weight: 0.520 g

Component	Substance Description	CAS# or Description	% of Component	Use in Product	Component Weight/ Substance Weight (in grams)	Component % of Total
Silicon die					0.003864	0.743%
	Silicon	7440-21-3	99.70		0.003850	
	Aluminium (Al)	7429-90-5	0.20		0.000010	
	Copper (Cu)	7440-50-8	0.05		0.000002	
	Titanium	7440-32-6	0.05		0.000002	
Lead-frame alloy					0.109820	21.119%
	Copper (Cu)	7440-50-8	97.25		0.106800	
	Iron (Fe)	7439-89-6	2.35		0.002580	
	Zinc (Zn)	7440-66-6	0.12		0.000130	
	Iron Phosphide (FeP)	26508-33-8	0.08		0.000090	
	Silver (Ag)	7440-22-4	0.20		0.000220	
Lead-frame plating					0.002390	0.460%
	Nickel (Ni)	7440-02-0	91.70		0.002190	
	Palladium (Pd)	7440-05-03	5.85		0.000140	
	Gold (Au)	7440-57-5	2.45		0.000060	
Die Attach Material					0.000760	0.146%
	Silver	7440-22-4	79.00		0.000600	
	Bismaleimide and acrylate polymer	Trade Secret	14.00		0.000110	
	Acrylate monomer	Trade Secret	7.00		0.000050	
Gold Wire					0.000670	0.129%
	Gold	7440-57-5	100.00		0.000670	
Mold Compound Encapsulation					0.402500	77.404%
	Epoxy Resin	Trade Secret	8.00		0.032200	
	Phenol Resin	Trade Secret	8.00		0.032000	
	Silicon Dioxide	60676-86-0	83.50		0.336090	
	Carbon Black	1333-86-4	0.50		0.002010	

Revision History

The following table shows the revision history for this document.

Date	Version	Description of Revisions
3/21/06	1.0	Initial Xilinx release.
7/10/06	1.1	100% Material Declaration
9/29/06	1.2	Updated component descriptions
12/10/07	2.0	Material content change per XCN07015
03/18/11	3.0	Material content change per XCN9026
12/23/11	4.0	Datecode change

Notice of Disclaimer

Xilinx regards this materials data to be correct but makes no guarantee as to its accuracy or completeness, including, but not limited to, with respect to its compliance with applicable environmental laws and regulations. Xilinx subcontracts the production, test and assembly of hardware devices to independent third-party vendors and materials suppliers (“Contractors”). All data provided hereunder is based on information received from Contractors. Xilinx has not independently verified the accuracy or completeness of this information which is provided solely for your reference in connection with the use of Xilinx products.